Green Acres Program

Local Assistance Program for County, Municipal and Nonprofit Acquisition or Stewardship Surveys **SURVEY REVIEW CHECKLIST**

SEE Scope of Work for Professional Land Surveying Services

Blank or Check indicates <u>satisfactory</u> submission. Circled section number indicates <u>deficiency</u>.

1.0	GENERAL INFORMATION	Date
	PURPOSE AND INTENT	Review BySellers Name
	BACKGROUND	Sellers Name
2.0	DEFINITIONS	Project Manager
Ple	ease review following definitions:	Project Name
	_	Project NameProject NumberFirm Name
		Firm Name
		Surveyor
		•
3.0	SCOPE OF WORK - Scope of Work for Profes	sional Land Surveying Services
	3.1 REFERENCE TO LAWS	
	3.2 REFERENCE TO SPECIFICATIONS	
	3.3 BASIS OF BEARINGS	
	TYPES OF SURVEY ACTIVITIES	
	3.4.2 PROPERTY SURVEYS	
	GREEN ACRES GUIDELINES FOR LAND SURVEYS	
	3.1 GENERAL REQUIRMENTS FOR ALL WORK	
	3.5.1.1 RESPONSIBILITY FOR WORK	
	3.5.1.2 SUPERVISION	
	3.5.1.3 RESEARCH	LITIEC
	3.5.1.4 FIELD PROCEDURES AND CREW RESPONSIBI 3.5.1.5 COST ESTIMATING	LITIES
	3.5.1.6. NOTIFICATIONS	
	5.2 GENERAL LAND SURVEY REQUIREMENTS AND A	ACOUISITION CONCEPTS
	3.5.2.1 GREEN ACRES GUIDELINES FOR LAND SURV	
_	3.5.2.2 SURVEY REPORT	
_	3.5.2.5 MUNICIPAL TAX LOTS	
	3.5.2.6 SURVEY TO FOLLOW DEED LINES	
	3.5.2.7 PUBLIC ROAD RIGHTS-OF-WAY AND RIVERS	
	3.5.2.8 PRIVATE RIGHTS-OF-WAY AND EASEMENTS	
	3.5.2.9 DEED CONFLICTS	
	3.5.2.9.1 RECORD GORE AREAS	
	3.5.2.9.2 RECORD OVERLAP AREAS	
	3.5.2.10 CORNER MARKING AND LINE MARKING	
	3.5.2.10.1 SETTING CORNER MARKERS	
	3.5.2.10.2 OMITTING MARKERS 3.5.2.10.3 FOUND MARKERS	
	3.5.2.10.4 OFFSET MARKERS	
	3.5.2.10.5 PUBLIC ACCESS CORNER MARKERS	
	3.5.2.10.6 THREE MONUMENT MINIMUM	
	3.5.2.10.7 CAP DETAIL	
	3.5.2.10.8 ACCEPTABLE CORNER MARKERS	
	3.5.2.10.8.1 DISKS 3.5.2.10.8.2 MONUMENTS	
_	3.5.2.10.8.4 REBAR	
	3.5.2.11 ORIGINAL SIGNATURE AND SEAL	
	3.3 SPECIFIC STANDARDS FOR PLAN OF SURVEY	
	3.5.3.1 PLAN SIZE	
	3.5.3.2 ORIENTATION	
	3.5.3.3 CLOCKWISE BEARINGS	
	3.5.3.4 SCALE	
	3.5.3.5 LINE AND CURVE TABLES	
	3.5.3.6 SIGNIFICANT FIGURES	
	3.5.3.7 MATHEMATICAL CLOSURE	

□ 3.5.3.8 MATHEMATICAL SURVEY EXPRESSIONS

	3.5.3.9 AREA
	3.5.3.10 AERIAL PHOTOGRAPHS AND PLANIMETRIC MAPPING
	3.5.3.11 AREAS OF CLAIM OF TIDELANDS OWNERSHIP BY STATE OF NEW JERSEY
	3.5.3.12 WATERWAYS
	3.5.3.13 ROADS
	3.5.3.14 SUBDIVISION OF LANDS
	3.5.3.15 TITLE BLOCK
	3.5.3.16 LEGEND OF ACQUISITION
	3.5.3.17 CORNER MARKING
	3.5.3.18 PLAN CERTIFICATION
	3.5.3.19 LOCATION MAP
	3.5.3.20 LINE WEIGHT AND TYPE 3.5.3.21 MISCELLANEOUS ITEMS ON PLAN
	3.5.3.21 MISCELLANEOUS IT ENIS ON FLAN 3.5.3.21.1 Street address of the subject parcel being surveyed only if the municipality has assigned a common street number;
_	3.5.3.21.1 Street address of the subject parcel being surveyed only if the intimerpanty has assigned a common street number, 3.5.3.21.2 Tax Block and Lot number of the parcel being surveyed, and those of adjoiners; Note: If the survey findings
_	indicate that the tax map is erroneous, so state. If a lot is not shown on the map, the lot shall be designated on the survey plan
	with the correct block number from the tax map and shall be identified as having NO LOT NUMBER ASSIGNED.
	3.5.3.21.3 Any permanent type buildings, paved or concrete improvements, structures or foundations must be shown. In
	particular, residences must be identified and labeled in coordination with the Using Agency.
	3.5.3.21.4 Any utility easements, visible or known of record, overhead wires or pole lines within the parcel being surveyed
	must be identified and shown on the plan of survey. If such easements are within the lines of a dedicated public road right-of-
	way, they may be omitted.
	3.5.3.21.5 Encroachments shall be clearly drawn, labeled and dimensioned to the property line. A detailed enlargement of
	any encroachment may be necessary to clearly show sheds, buildings, decks, or other structures or areas of adverse use such as
	stone parking areas or areas of mowed lawn.
	3.5.3.21.6 Watercourses , including the name and showing the direction of flow and area contained within the bed must be
	drawn and labeled on the plan. In particular, water bodies located on the boundary of the property must be shown in a hatched pattern on the plan, and the area calculated and stated on the plan.
	3.5.3.21.7 Show all drains and sewers that are visible on the surface of and within the limits of the parcel. Drains and
_	sewers within a dedicated public road right-of-way need not be shown.
	3.5.3.21.8 Provide the name of record owners and the latest deed book and page reference for adjoining
	lands to indicate that those records had been examined in the survey process and that there are no areas of confusion in the
	record, except for those that may be shown on the plan, if any.
	3.5.3.21.9 Roads not open are to be so indicated. Paper streets that have not been vacated are subject to possible public and
	or private rights, and the area contained by them must be indicated on the plan.
	3.5.3.21.10 If the survey indicates that the municipal tax map erroneously locates the parcel, this discrepancy should be
	noted on the plan.
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes,
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company.
	 3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983
	 3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in
	 3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived
	 3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited.
0	 3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT
0	 3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION"
0 0000	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH
0 000000	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set
0 0000000	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES
0 00000000	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION SECOND PARAGRAPH 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED 3.5.4.9 CLOSING PARAGRAPH AND CALL FOR SURVEY
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED 3.5.4.9 CLOSING PARAGRAPH AND CALL FOR SURVEY 3.5.4.10 ORIGINAL SIGNATURE, EMBOSSED SEAL AND DATE SIGNED
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4.1 DEED DESCRIPTION FORMAT 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED 3.5.4.9 CLOSING PARAGRAPH AND CALL FOR SURVEY 3.5.4.10 ORIGINAL SIGNATURE, EMBOSSED SEAL AND DATE SIGNED DELIVERABLES (ONLY AS REQUIRED SUBMISSION TO GREEN ACRES)
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4 DEED DESCRIPTION FORMAT 3.5.4.1 DEED DESCRIPTION TYPE 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION INTRODUCTION 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED 3.5.4.9 CLOSING PARAGRAPH AND CALL FOR SURVEY 3.5.4.10 ORIGINAL SIGNATURE, EMBOSSED SEAL AND DATE SIGNED
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NJPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4.1 DEED DESCRIPTION FORMAT 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.5 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED 3.5.4.9 CLOSING PARAGRAPH AND CALL FOR SURVEY 3.5.4.10 ORIGINAL SIGNATURE, EMBOSSED SEAL AND DATE SIGNED DELIVERABLES (ONLY AS REQUIRED SUBMISSION TO GREEN ACRES) Two (2) FULL-SIZE PAPER COPIES OF SURVEY PLAN ORIGINAL SIGNATURE & FOLDED
	3.5.3.21.11 The deed book and page number of the reference deeds actually used must be indicated in the graphic portion of the plan to which they apply. This information shall not be excluded or limited in appearance through the use of notes, except that the Contractor may limit its search of records to the obvious and reasonable (after consultation with the Using Agency), and may produce a plan noting that the work is subject to the findings of an accurate and up-to-date title search by a competent title company. 3.5.3.21.12 The point of beginning used in the metes and bounds description must be clearly labeled "Description Point of Beginning" or "P.O.B." or similar notation, and must be tied into a corner of record or road intersection. The NIPCS NAD 1983 Northing and Easting coordinate values stated in US Survey Feet to two decimal places must be labeled on the plan and stated in the description. The Contractor must set a monument at the point of beginning for each parcel, unless this requirement is waived or modified by the Using Agency at the time that the bids for a Site-Specific Engagement are solicited. 3.5.4.1 DEED DESCRIPTION FORMAT 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.2 LETTERHEAD OF SURVEY FIRM 3.5.4.3 DESCRIPTION HEADING "DEED DESCRIPTION" 3.5.4.4 DESCRIPTION SECOND PARAGRAPH 3.5.4.6 BODY OF DESCRIPTION include reference to the Corner Number for corner markers set 3.5.4.7 USING AUGMENTING AND QUALIFYING CLAUSES 3.5.4.8 RECITE AREAS DESCRIBED 3.5.4.9 CLOSING PARAGRAPH AND CALL FOR SURVEY 3.5.4.10 ORIGINAL SIGNATURE, EMBOSSED SEAL AND DATE SIGNED DELIVERABLES (ONLY AS REQUIRED SUBMISSION TO GREEN ACRES) Two (2) FULL-SIZE PAPER COPIES OF SURVEY PLAN ORIGINAL SIGNATURE & FOLDED TWO (2) METES AND BOUND DESCRIPTION AND REDUCED SURVEY PLAN ATTACHED